



Low noise & Low recoil

Acc Pg. A194

 Ideal for installing fiber cement and wood shingle siding, sub-floor framing, exterior nailing, interior nailing, framing

Specifications:-	
Capacity	Length: 38 - 65 mm
Nail gauge	Gauge: 2.3 - 2.5 mm
	70 - 120 psi
Operating Pressure	0.49 - 0.83 MPa (70 - 120 PSI)
Magazine Capacity	200 - 300
Dimensions (L x W x H)	250x70x256 mm
Net weight	2.2 kg

Standard Equipment: Safety Goggles, Nose Adapter, Hook, Hex Wrench

SAWING Pneumatic Micro Pinner ROUTERING / PLANING Precision and accuracy in every shot • Durable and lightweight die cast housing CLEANING Rubber handle • Uses 23 gauge pins from 15/32" to 1" (12 mm to 25 mm) HEAT GUN / LASERS **Specifications:-**K 65 PSIG (4.5 kgf / cm² G) **Operating air pressure** Pin size Gauge : 23 (0.63 mm) (0.025") Length : 12 - 25 mm (15/32" - 1") PNEUMATIC TOOLS Pin capacities 100 Overall length 240 mm (9.6") Net weight 0.9 kg (1.98 lbs) GARDEN TOOLS GENERATORS Standard Equipment: Oil Supply, Hex Wrench

AF201Z

