CORDLESS	DDF486 13mm		Acc Pg. A024-060
	18V LXT - Lithium-Ic	on Cordless Driver Drill	
			TRESK
		NEW PRODUCT	
FIXING /			AR 7
ASTENING			
	BL XPT		Pankini
	MOTOR 249 B		
DRILLING /	Increased performa	ance in continuous hea	vy-duty applications
DRILLING	 Increased max clutch to 	rque enables to adjust clutch	torque even when
	tightening fasteners into	hard material	·
	Durable aluminium gear		
		5	
	 Mechanical 2 speed gea 	aring with all metal gear const	truction
		5	
DRILLING /	XPT technology that pro	otects against dust & moisture	
DRILLING / MOLITION	55 1	otects against dust & moisture c design at only 178 mm long	2
	55 1	5	2
	Compact and ergonomic	5	
	Compact and ergonomic 21 torque settings Specifications:-	c design at only 178 mm long	
MOLITION	Compact and ergonomie 21 torque settings	c design at only 178 mm long	
CUTTING	Compact and ergonomic 21 torque settings Specifications:-	c design at only 178 mm long	
CUTTING MASONRY/	Compact and ergonomi 21 torque settings Specifications:- Capacity	c design at only 178 mm long	
CUTTING MASONRY/	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity	c design at only 178 mm long	
CUTTING MASONRY/	Compact and ergonomi 21 torque settings Specifications:- Capacity	c design at only 178 mm long	
CUTTING MASONRY/ METAL]	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity No Load Speed (RPM)	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Wo Siding Board: 170 mm 1.5 - 13 mm (1/16 - 1/2") High / Low: 0 - 2,100 / 0 - 550	
CUTTING MASONRY/	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity No Load Speed (RPM) Max Fastening Torque	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Wo Siding Board: 170 mm 1.5 - 13 mm (1/16 - 1/2") High / Low: 0 - 2,100 / 0 - 550 Hard / Soft: 130 / 65 N·m	
CUTTING MASONRY/ METAL]	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity No Load Speed (RPM) Max Fastening Torque Dimensions (L x W x H)	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Woo Siding Board: 170 mm Woo	
CUTTING MASONRY/ METAL]	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity No Load Speed (RPM) Max Fastening Torque Dimensions (L x W x H) Net weight	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Woo Siding Board: 170 mm Woo	
CUTTING MASONRY/ METAL]	Compact and ergonomi 21 torque settings Specifications:- Capacity Chuck Capacity No Load Speed (RPM) Max Fastening Torque Dimensions (L x W x H) Net weight	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Wo Siding Board: 170 mm 1.5 - 13 mm (1/16 - 1/2") High / Low: 0 - 2,100 / 0 - 550 Hard / Soft: 130 / 65 N-m 178 x 81 x 265 mm 2.6 kg) bit, Belt clip	
CUTTING IASONRY/ METAL]	Compact and ergonomi 21 torque settings Specifications:- Capacity No Load Speed (RPM) Max Fastening Torque Dimensions (L x W x H) Net weight Standard Equipment: (+)(-	c design at only 178 mm long Steel: 13 mm Wood (Auger-Bit): 50 mm Wo Siding Board: 170 mm 1.5 - 13 mm (1/16 - 1/2") High / Low: 0 - 2,100 / 0 - 550 Hard / Soft: 130 / 65 N-m 178 x 81 x 265 mm 2.6 kg) bit, Belt clip AVAILABLE VARIANTS	D od (Self-Feed Bit): 76 mm



Standard Equipment: (+)(-) bit, Side grip

AVAILABLE VARIANTS		
5.0Ah	3.0Ah	"Z" VARIANT
DDF481 RTJ INCLUDES 2 BATTERIES / 1 CHARGER / MAKPAC CONNECTOR CASE	DDF481 RFJ INCLUDES 2 BATTERIES / 1 CHARGER / MAKPAC CONNECTOR CASE	DDF481 Z TOOL ONLY (DOES NOT INCLUDE BATTERY / CHARGE / CARRYING CASE)

co

[COI

ROUTERING /

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS	

DDF484 RTJ INCLUDES 2 BATTERIES / 1 CHARGER / MAKPAC CONNECTOR CASE

DDF484 13mm			Acc Pg. A024-060
18V LXT - Lithium-lo (18V) (180) (n Cordless Driv	er Drill	
Powerful Brushless • Delivers more drilling, di • Aluminum gear housing • Variable 2-speed for a w • Built-in twin LED lights w area	riving and fastening creates an impressio ride range of drilling	speed on of rigid and faste	ity and luxuriousness
Specifications:-	\$\$ \$\$ \$\$ \$\$	m 100 I =	D
Capacity	Steel / Woo	d: 13 / 38 m	 1m
Chuck capacity	1.5 - 13 mm		
No Load Speed (RPM)	High / Low:	0 - 2,000 /	0 - 500
Max Fastening Torque	Hard / Soft:	54 / 30 N r	n
Dimensions (L x W x H)	172x79x26	1 mm	
Net weight	1.8 kg		
Standard Equipment: (+)(-) bit, Belt clip AVAILABLE VARIAN	ITS	
5.0Ah	3.0Ah		"Z" VARIANT

DDF453 13mm	Acc Pg. A024-060
18V LXT - Lithium-Ion Cordless Driver Drill	M
All metal gear construction ensures high t	ransmission

durability

- Single sleeve keyless chuck enables easy bit installation/removal with one hand.
- Ergonomically designed rubberized soft grip provides more control and

comfort.

Specifications:-\$\$⊕**₩**2**m**®=D

Capacity	Steel: 13 mm / Wood: 36 mm
No load speed (rpm)	High: 0-1,300 / Low: 0-400
Max. fastening torque	Hard / Soft: 42 / 27 N m
Dimensions (L x W x H)	222x79x244 mm
Net weight	2 kg

Standard Equipment: (+)(-) bit, Belt clip

AVAILABLE VARIANTS		
5.0Ah	3.0Ah	"Z" VARIANT
-	DDF453 RFE INCLUDES 2 BATTERIES / 1 CHARGER / PLASTIC CARRYING CASE	-

SANDING / POLISHING

SAWING

PLANING