

HR2475 24mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **419** 

Combination Hammer




2.7 JOULES

High durability in mechanical parts, motor and carbon brush.

- 3 operation modes - hammering, hammering with rotation, and rotation only.
- Ergonomic D-shaped handle with rubberized soft grip provides more comfort and better control while minimizing hand fatigue and pain.
- One-touch sliding chuck for easy bit changes.

Specifications:- 

Continuous rating input	780W
Capacity	Concrete : 24mm (15/16") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
Impacts per minute (ipm)	0-4,500
No load speed (rpm)	0-1,100
Sound pressure level	89dB(A)
Sound power level	100dB(A)
Vibration level	Chiseling: 10.5m/s ² / hammer drilling: 15.5m/s ² Drilling: 3m/s ²
Dimensions (L x W x H)	429x84x158mm (16-7/8"x3-5/16"x6-1/4")
Net weight	3.0kg (6.6lbs)
Power supply cord	4.0m (13.1ft)

Standard Equipment: Side Handle, Depth Gauge. (Tool does not come with bit)

HR2600 26mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **325** 

Rotary Hammer




2.9 JOULES

2 Operation Modes: Hammering with rotation & Rotation only.

- Reverse function on brush holder.
- Large trigger switch.

Specifications:- 

Continuous rating input	800W
Capacity	Concrete : 26mm (1") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
Impacts per minute (ipm)	0 - 4,600
No load speed (rpm)	0 - 1,200
Sound pressure level	91dB(A)
Sound power level	102dB(A)
Vibration level	Hammer drilling: 15.5m/s ² / Drilling: 2.5m/s ²
Dimensions (L x W x H)	361x77x209mm (14-1/4"x3"x8-1/4")
Net weight	2.8kg (6.2lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Side Grip, Depth Gauge. (Tool does not come with bit)

HR2630 26mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **325** 

Combination Hammer




2.9 JOULES


Easy-to-grip handle ergonomically designed to give maximum power thrust.

- 3 operation modes - hammering, hammering with rotation, rotation.
- Less bit wobbling.
- One-touch sliding chuck for easy bit change.
- Operation mode change lever positioned on the bottom of gear housing for reduced possibility of breakage.



Specifications:- 

Continuous rating input	800W
Capacity	Concrete : 26mm (1") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
Impacts per minute (ipm)	0-4,600
No load speed (rpm)	0-1,200
Sound pressure level	91dB(A)
Sound power level	102dB(A)
Vibration level	Hammer drilling: 15.5m/s ² / Chiseling: 9.5m/s ² Drilling: 2.5m/s ²
Dimensions (L x W x H)	361x77x209mm (14-1/4"x3"x8-1/4")
Net weight	2.8kg (6.2lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Side Grip, Depth Gauge. (Tool does not come with bit)

HR2630T 26mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **325** 


Combination Hammer

2.9 JOULES

Easy-to-grip handle ergonomically designed to give maximum power thrust

- 3 operation modes - hammering, hammering with rotation, rotation.
- Less bit wobbling.
- One-touch sliding chuck for easy bit change.
- Operation mode change lever positioned on the bottom of gear housing for reduced possibility of breakage.
- Quick change drill chuck from SDS-plus to 3 jaw chuck literally in a second

Specifications:- 

Continuous rating input	800W
Capacity	Concrete : 26mm (1") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
Impacts per minute (ipm)	0-4,600
No load speed (rpm)	0-1,200
Sound pressure level	91dB(A)
Sound power level	102dB(A)
Vibration level	Hammer drilling: 15m/s ² / Chiseling: 9.5m/s ² Drilling: 2.5m/s ²
Dimensions (L x W x H)	385x77x209mm (15-1/8"x3"x8-1/4")
Net weight	3.0kg (6.6lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Quick change drill chuck, Side grip, Depth gauge (Tool does not come with bit)

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE / MASONRY / METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS