PO6000C 150 mm (6")



Random Orbit Polisher





Selectable two rotation mode: Random orbit with forced rotation mode for rough polishing & Random orbit mode for fine polishing

- Random orbit with forced rotation mode is orbital action with forced rotation of the pad for rough polishing such as surface treatment
- Random orbit mode is orbital action with free rotation of the pad for fine polishing
- Setting up RPM in the full speed is easy by a variable speed dial



Continuous rating input	900W
Pad Size	150 mm (6")
Orbits Per Minute (OPM)	0 - 6,800
Strokes Per Minute (SPM)	0 - 13,600
No Load Speed (RPM)	0 - 780
Orbit Diameter	5.5 mm (7/32")
Vibration Level	Polishing: 7.0 m/s ²
Sound Pressure Level	83 dB(A)
Sound Power Level	94 dB(A)
Dimensions (L x W x H)	451x148x126 mm (17-3/4"x5-7/8"x5")
Net weight	2.8 kg (6.2 lbs)
Power supply cord	4.0 m (13.1 ft)

Standard Equipment: Side grip, Hex Wrench

PV7000C 180mm (7")

Polisher

9237CB 180mm (7")



Polisher





Loop handle with rubberized soft grip.

- Variable speed control by dial Rotation speed is adjustable to application.
- Vent dust cover of screw-down type prevents ingress of wool fibers.
- Elastomer bumper on gear housing protects a precious surface, such as that of car body, from damage and scratches



Continuous rating input	1,200W
Capacity	Wool Pad: 180 mm (7")
	Wool Bonnet: 180 mm (7")
No Load Speed (RPM)	0 - 3,200
Vibration Level	2.5 m/s² or less
Sound Pressure Level	83 dB(A)
Sound Power Level	94 dB(A)
Dimensions (L x W x H)	431x198x187 mm (17"x7-3/4"x7-3/8")
Net weight	3.4 kg (7.5 lbs.)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment: Loop handle, Hex wrench

DRILLING / FIXING

CONCRETE DRILLING / DEMOLITION

MIXING / STIRRING

CUTTING (CONCRETE / METAL)

GRINDING

SANDING /
POLISHING

SAWING

MULTI-TOOL

ROUTERS / PLANERS

NAILERS / STAPLERS

HEAT GUN /

CLEANING

OPE

JOBSITE TOOLS

HAND TOOLS /
COMBINATION SET

TOOL HOLDERS AND POUCHES / MAKPAC SYSTEM

9218PB 180mm (7")






100wī



Compact body with low center of gravity for absolutely controlled operation and reduced fatigue

- Electronic control for consistent speed
- 2 speed plus variable speed control for a wide range of polishing works
- Pre-setting speed control dial
- Durable cord guard
- Quick-flip speed change for compounding and polishing



Standard Equipment: Wrench, Side Grip

Continuous rating Input	900W
Capacity	Abrasive disc : 180mm (7")
	Pad : 170mm (6-11/16")
No load speed	600-2,000rpm
Overall length	210mm (8-1/4")
Net weight	2.1kg (4.6lbs)
Power supply cord	2.5m (8.2ft)

• Easy handling to reduced operator fatigue

ı		
	Continuous rating Input	570W
ĺ	Capacity	Wool bonnet : 180mm (7")
ĺ	No load speed	2,000rpm
l	Overall length	235mm (9-1/4")
ĺ	Net weight	2.7kg (5.9lbs)
İ	Power supply cord	2.5m (8.2ft)

Better polishing action for a wide range of applications

Standard Equipment: Lock Nut Wrench, Grip