


4329 

Jig Saw




Light duty model with continuous input 450W

- 3 orbital settings plus straight cutting
- Variable speed control dial (500-3,100 SPM) enables user to match the speed to the application for optimal cutting performance in a variety of materials.
- Through-the-body dust port provides optimal dust management with use of clear dust cover and vacuum.
- Bevel cuts to 45° right or left and positive stop at 90° for solid cutting performance


 **64 mm**

Continuous rating Input	450W
Capacity	In wood at 0 degrees : 65mm (2-9/16") In steel at 90 degrees : 6mm (1/4")
Length of stroke	18mm (11/16")
Strokes per minute (spm)	500 - 3,100
Dimensions (L x W x H)	224 x 77 x 197mm (8-7/8" x 3" x 7-3/4")
Net weight	1.8kg (4.0lbs)
Power supply cord	2.0m (6.6ft)

Standard Equipment: Hex Wrench


4350CT 

Jig Saw




Tool less blade change system (with electronic control + speed dial)

- Electronic speed control maintains consistent speed set for various work piece
- 3 orbital settings plus straight cut
- Plastic cover plate can be attached without tool
- Low vibration and low noise level


 **419 mm**

Continuous rating Input	720W
Capacity	In wood at 90 degrees : 135mm (5-5/16") In steel at 90 degrees : 10mm (3/8")
Length of stroke	26mm (1")
Strokes per minute	800 - 2,800 spm
Dimensions (L x W x H)	236 x 73 x 207mm (9-1/4" x 2-7/8" x 8-1/8")
Net weight	2.4kg (5.3lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Hex Wrench, Cover Plate, Anti-Splintering Device


4350FCT 

Jig Saw




Tool less blade change system (with electronic control + speed dial)

- Electronic speed control maintains consistent speed set for various work piece
- 3 orbital settings plus straight cut
- Plastic cover plate can be attached without tool
- Low vibration and low noise level
- Built-in LED job light for easy tracing of cutting line


 **419 mm**

Continuous rating Input	720W
Capacity	In wood at 90 degrees : 135mm (5-5/16") In steel at 90 degrees : 10mm (3/8")
Length of stroke	26mm (1")
Strokes per minute	800 - 2,800 spm
Dimensions (L x W x H)	236 x 73 x 207mm (9-1/4" x 2-7/8" x 8-1/8")
Net weight	2.4kg (5.3lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Hex Wrench, Cover Plate, Anti-Splintering Device


4351FCT 

Jig Saw



Toolless blade change system (with electronic control + speed dial)

- Electronic speed control maintains consistent speed set for various work piece
- 3 orbital settings plus straight cut
- Built-in LED job light for easy tracing of cutting line.
- Ergonomically designed handle with soft grip provides more control and comfort.
- Low vibration and low noise level

 **419 mm**

Continuous rating input	720W
Capacity	Wood : 135mm (5-5/16") Steel : 10mm (3/8")
Length of stroke	26mm (1")
Strokes per minute (spm)	800 - 2,800
Dimensions (L x W x H)	271x73x187mm (10-11/16" x 2-7/8" x 7-3/8")
Net weight	2.5kg (5.5lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Hex wrench, Cover plate, Anti-splintering device

- DRILLING / FIXING
- CONCRETE DRILLING / DEMOLITION
- MIXING / STIRRING
- CUTTING (CONCRETE / METAL)
- GRINDING
- SAWING / POLISHING
- SAWING
- MULTI-TOOL
- ROUTERS / PLANERS
- NAILERS / STAPLERS
- HEAT GUN / LASER
- CLEANING
- OPE
- JOB SITE TOOLS
- SPECIALTY TOOLS
- HAND TOOLS / COMBINATION SET
- TOOL HOLDERS AND POUCHES / MAKPAC SYSTEM