




DS4011 13mm (1/2") Acc Pg. A037-060 **411** 



Drill






New aesthetic design.

- High performance.
- Full 360 degree rotatable D-handle with 24 positive stops for multi-position operation.


Specifications:-  


| | |
|-------------------------|-----------------------------|
| Continuous rating Input | 750W |
| Capacity | Steel : 13mm Wood : 36mm |
| No load speed | 600 rpm |
| Dimensions (L x W x H) | 340 x 83 x 401 mm |
| Net weight | 2.8kg |
| Power supply cord | 2.5m |

Standard Equipment: Chuck Key, Side Grip

DS5000 16mm (5/8") Acc Pg. A037-060 **411** 



Drill






New aesthetic design with 16mm drilling capacity.

- High performance.
- Full 360 degree rotatable D-handle with 24 positive stops for multi-position operation.


Specifications:-  


| | |
|-------------------------|-----------------------------|
| Continuous rating input | 750W |
| Capacity | Steel: 16 mm Wood: 36 mm |
| No Load Speed (RPM) | 600 |
| Dimensions (L x W x H) | 348x83x401 mm |
| Net weight | 3.0 kg |
| Power supply cord | 2.5 m |

Standard Equipment: Chuck Key, Side Grip

6016 16mm (5/8") Acc Pg. A037-060 **51** 

Drill





Power and torque packed in rugged aluminum body for heavy duty applications.

- D-handle rotates 360 degrees for multi-position operation.
- Heavy-duty industrial chuck.

Specifications:-

| | |
|-------------------------|---|
| Continuous rating Input | 480W |
| Capacity | Steel : 16mm (5/8") Wood : 36mm (1-3/8") |
| No load speed | 700rpm |
| Overall length | 365mm (14-3/8") |
| Net weight | 4.1kg (9.0lbs) |
| Power supply cord | 2.5m (8.2ft) |

Standard Equipment: Chuck Key, Grip, Depth Gauge

6305 13mm (1/2") Acc Pg. A037-060 **303** 

Drill





Rear handle with soft rubber grip, ergonomically designed for comfortable operation

- Warning lamp that indicates trouble with the cord, the switch or the motor
- Designed for installation on Type-43 drill stand.
- Double Insulated Construction

Specifications:- 

| | |
|-------------------------|--|
| Continuous rating input | 850W |
| Capacity | Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") |
| No Load Speed (RPM) | 1,450 |
| Dimensions (L x W x H) | 346x84x152 mm |
| Net weight | 2.8 kg |
| Power supply cord | 2.5 m |

Standard Equipment: Chuck Key, Depth Gauge Assembly, Grip.

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS