| SA7000C 180mm (7") | |
|--|--|
| Angle Sander | |
| Powerful 1.600W moto | or delivers outstanding performance |
| for industrial use | 51 |
| | variation of the protect from everybooting |
| Motor has outstanding heat | |
| 5 | t resistance to protect from overheating |
| Speed control dial allows yo | to adjust maximum speed in 6 stages from 1,500 |
| • Speed control dial allows yo to 4,000rpm | ou to adjust maximum speed in 6 stages from 1,500 |
| Speed control dial allows yo | ou to adjust maximum speed in 6 stages from 1,500 |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc | ou to adjust maximum speed in 6 stages from 1,500 |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc | ou to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera | ou to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera | bu to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. Itor fatique in continuous use. |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera Specifications:- | u to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. utor fatique in continuous use. |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera Specifications:- Continuous rating Input Capacity | u to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. ator fatique in continuous use. |
| Speed control dial allows you to 4,000rpm Variable speed trigger switce Lightweight, reducing opera Specifications:- Continuous rating Input Capacity No load speed | bu to adjust maximum speed in 6 stages from 1,500 controlled sanding. stor fatique in continuous use. 1,600W Abrasive disc : 180mm (7") Pad : 180mm (7") 0-4,000rpm |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera Specifications:- Continuous rating Input Capacity | bu to adjust maximum speed in 6 stages from 1,500 controlled sanding. ator fatique in continuous use. 1,600W Abrasive disc : 180mm (7") Pad : 180mm (7") 0-4,000rpm 453mm x 170mm x 136mm |
| Speed control dial allows yo to 4,000rpm Variable speed trigger switc Lightweight, reducing opera Specifications:- Continuous rating Input Capacity No load speed Dimensions | u to adjust maximum speed in 6 stages from 1,500 h for controlled sanding. tor fatique in continuous use. 1,600W Abrasive disc : 180mm (7") Pad : 180mm (7") 0-4,000rpm 453mm x 170mm x 136mm (17-7/8" x 6-11/16" x 5-3/8")) |
| Speed control dial allows you to 4,000rpm Variable speed trigger switce Lightweight, reducing opera Specifications:- Continuous rating Input Capacity No load speed | bu to adjust maximum speed in 6 stages from 1,500 controlled sanding. ator fatique in continuous use. 1,600W Abrasive disc : 180mm (7") Pad : 180mm (7") 0-4,000rpm 453mm x 170mm x 136mm |





