CORDLESS

FIXING /

DRILLING /

CONCRETE DRILLING /

CUTTING
[CONCRETE/ MASONRY/

MULTI TOOL

SANDING / POLISHING

SAWING



Angle Grinder - 840W (Slide Switch)			Acc Pg. A099-128 325 MM
	9556HN 100mm (4")	9557HN 115mm (4-1/2")	9558HN 125mm (5")
Continuous rating Input	840W	840W	840W
Capacity	Depressed center wheel: 100mm (4")	Depressed center wheel: 115mm (4-1/2")	Depressed center wheel: 125mm (5")
	Abrasive disc: 100mm (4")	Abrasive disc: 115mm (4-1/2")	Abrasive disc: 125mm (5")
	Diamond wheel: 100mm (4")	Diamond wheel: 115mm (4-1/2")	Diamond wheel: 125mm (5")
No load speed	11,000rpm	11,000rpm	11,000rpm
Dimensions	271mm x 129mm x 106mm	271mm x 129mm x 106mm	271mm x 139mm x 106mm
(L x W x H)	(10-5/8" x 5-1/8" x 4-3/16")	(10-5/8" x 5-1/8" x 4-3/16")	(10-5/8" x 5-1/2" x 4-3/16")
Spindle thread	DIN type	DIN type	DIN type
Net weight	2.0kg (4.4lbs)	2.0kg (4.4lbs)	2.1kg (4.6lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)

High performance motor and high heat resistance.

- Labyrinth construction protects all ball bearings from dust and debris.
- \bullet Small circumference barrel grip for easy handling.
- Shaft lock for easy wheel changes.
- Easier repairing of gear section assembled with key.

Standard Equipment: Lock Nut Wrench, Grip.



Angle Grinder - 840W (Paddle Switch)			Acc Pg. A099-128 325 MM
	9556HP 100mm (4")	9557HP 115mm (4-1/2")	9558HP 125mm (5")
Continuous rating Input	840W	840W	840W
Capacity	Depressed center wheel: 100mm (4")	Depressed center wheel: 115mm (4-1/2")	Depressed center wheel: 125mm (5")
	Abrasive disc: 100mm (4")	Abrasive disc: 115mm (4-1/2")	Abrasive disc: 125mm (5")
	Diamond wheel: 100mm (4")	Diamond wheel: 115mm (4-1/2")	Diamond wheel: 125mm (5")
No load speed	11,000rpm	11,000rpm	11,000rpm
Dimensions	273mm x 129mm x 106mm	273mm x 129mm x 106mm	273mm x 129mm x 106mm
(L x W x H)	(10-3/4" x 5-1/8" x 4-3/16")	(10-3/4" x 5-1/8" x 4-3/16")	(10-3/4" x 5-1/8" x 4-3/16")
Spindle thread	DIN type	DIN type	DIN type
Net weight	2.1kg (4.5lbs)	2.1kg (4.5lbs)	2.1kg (4.5lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)
			2.511 (0.21)

Ergonomic paddle switch featured.

- Natural fit slim body to left and right hand for easy handling.
- Ergonomically designed paddle lever gives comfort to the fingers.
- Lock-off button built in the center of paddle lever.

Standard Equipment: Lock Nut Wrench, Grip.

CLEANING

ROUTERING /

PLANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS



Angle Grinder -	1,050W (Large Trigger Switch)	Acc Pg. A099-128 303
	9015B 125mm (5")	
Continuous rating Input	1,050W	
Capacity	Depressed center wheel: 125mm (5")	
	Wire cup brush: 90mm (3-1/2")	
	Abrasive disc: 125mm (5")	
No load speed	Diamond wheel : 125mm (5")	
Dimensions	10,000rpm	
(L x W x H)	381mm (15")	
Spindle thread	DIN type, 5/8"-11UNC	
Net weight	2.4kg (5.3lbs)	
Power supply cord	2.5m (8.2ft)	

Big trigger switch for convenient operation.

• Gear housing can be positioned at every 90 degrees.

Standard Equipment: Lock Nut Wrench, Grip.