


- DRILLING / FIXING
- CONCRETE DRILLING / DEMOLITION
- MIXING / STIRRING
- CUTTING (CONCRETE / METAL)
- GRINDING





Angle Grinder - 840W (Slide Switch)

	9556HN 100mm (4")	9557HN 115mm (4-1/2")	9558HN 125mm (5")
Continuous rating Input	840W	840W	840W
Capacity	Depressed center wheel: 100mm (4") Abrasive disc: 100mm (4") Diamond wheel: 100mm (4")	Depressed center wheel: 115mm (4-1/2") Abrasive disc: 115mm (4-1/2") Diamond wheel: 115mm (4-1/2")	Depressed center wheel: 125mm (5") Abrasive disc: 125mm (5") Diamond wheel: 125mm (5")
No load speed	11,000rpm	11,000rpm	11,000rpm
Dimensions (L x W x H)	271mm x 129mm x 106mm (10-5/8" x 5-1/8" x 4-3/16")	271mm x 129mm x 106mm (10-5/8" x 5-1/8" x 4-3/16")	271mm x 139mm x 106mm (10-5/8" x 5-1/2" x 4-3/16")
Spindle thread	DIN type	DIN type	DIN type
Net weight	2.0kg (4.4lbs)	2.0kg (4.4lbs)	2.1kg (4.6lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)


High performance motor and high heat resistance.

- Labyrinth construction protects all ball bearings from dust and debris.
- Small circumference barrel grip for easy handling.
- Shaft lock for easy wheel changes.
- Easier repairing of gear section assembled with key.

Standard Equipment: Lock Nut Wrench, Grip.

- SANDING / POLISHING
- SAWING
- MULTI-TOOL
- ROUTERS / PLANERS
- NAILERS / STAPLERS
- HEAT GUN / LASER





Angle Grinder - 840W (Paddle Switch)

	9556HP 100mm (4")	9557HP 115mm (4-1/2")	9558HP 125mm (5")
Continuous rating Input	840W	840W	840W
Capacity	Depressed center wheel: 100mm (4") Abrasive disc: 100mm (4") Diamond wheel: 100mm (4")	Depressed center wheel: 115mm (4-1/2") Abrasive disc: 115mm (4-1/2") Diamond wheel: 115mm (4-1/2")	Depressed center wheel: 125mm (5") Abrasive disc: 125mm (5") Diamond wheel: 125mm (5")
No load speed	11,000rpm	11,000rpm	11,000rpm
Dimensions (L x W x H)	273mm x 129mm x 106mm (10-3/4" x 5-1/8" x 4-3/16")	273mm x 129mm x 106mm (10-3/4" x 5-1/8" x 4-3/16")	273mm x 129mm x 106mm (10-3/4" x 5-1/8" x 4-3/16")
Spindle thread	DIN type	DIN type	DIN type
Net weight	2.1kg (4.5lbs)	2.1kg (4.5lbs)	2.1kg (4.5lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)


Ergonomic paddle switch featured.

- Natural fit slim body to left and right hand for easy handling.
- Ergonomically designed paddle lever gives comfort to the fingers.
- Lock-off button built in the center of paddle lever.

Standard Equipment: Lock Nut Wrench, Grip.

- CLEANING
- OPE
- JOBSITE TOOLS
- SPECIALTY TOOLS
- HAND TOOLS / COMBINATION SET
- TOOL HOLDERS AND POUCHES / MAKPAC SYSTEM



Angle Grinder - 1,050W (Large Trigger Switch)

	9015B 125mm (5")
Continuous rating Input	1,050W
Capacity	Depressed center wheel: 125mm (5") Wire cup brush: 90mm (3-1/2") Abrasive disc: 125mm (5") Diamond wheel: 125mm (5")
No load speed	10,000rpm
Dimensions (L x W x H)	381mm (15")
Spindle thread	DIN type, 5/8"-11UNC
Net weight	2.4kg (5.3lbs)
Power supply cord	2.5m (8.2ft)

Big trigger switch for convenient operation.

- Gear housing can be positioned at every 90 degrees.

Standard Equipment: Lock Nut Wrench, Grip.

