


- DRILLING / FIXING
- CONCRETE DRILLING / DEMOLITION
- MIXING / STIRRING
- CUTTING (CONCRETE / METAL)
- GRINDING
- SANDING / POLISHING
- SAWING

DCG180
18V | LXT

Cordless Caulking Gun



**Excellent work efficiency.**

- Variable speed control by dial and trigger switch for maximum control of sealant flow rate
- 300ml and 600ml size holder can be used
- Anti-drip function stops excess from oozing out just on release of the switch trigger
- Rubberized soft grip provides comfortable grip and better control



Max pushing force	5,000N
No load speed	0-28mm/sec. (0-66in/min.)
Dimensions (L x W x H)	404x108x281mm
Net weight	2.1kg

**Standard Equipment:** Holder Set A, Safety Goggles

AVAILABLE VARIANTS

"Z" VARIANT

**DCG180 ZK**  
 TOOL WITH PLASTIC CARRY CASE (DOES NOT INCLUDE BATTERY / CHARGER)

- MULTI-TOOL
- ROUTERS / PLANERS
- NAILERS / STAPLERS
- HEAT GUN / LASER
- CLEANING
- OPE
- JOBBSITE TOOLS
- SPECIALTY TOOLS
- HAND TOOLS / COMBINATION SET
- TOOL HOLDERS AND POUCHES / MAKPAC SYSTEM

Accessories

Standard Accessory - Set A

**300ml size Holder Holder Set A (Part No. 196351-8)**

360° rotatable cartridge holder 300 ml cartridges





Optional Accessory - Set B

**600ml size Holder Holder Set B (Part No. 1911T4-0)**

Holder B set





Holds (600ml) cartridge style, sausage style, bulk caulks and adhesives



Optional Accessory - Set D


**400ml size Holder Holder Set D (Part No. 191P89-6)**

Holds (400 ml) cartridge style, sausage style and bulk caulks


AC001G
40V MAX | XGT

Cordless Air Compressor



**Surrounding environment-friendly machine with low noise level**

- Rigid roll cage frame construction minimizes the chance of damage to the motor and compression units.
- Carry handle with rubberized grip designed for easy transportation
- Oil-free pump design
- Equipped with high operating efficiency motor



Tank	7.6 L (2 gal)
Cut-In Pressure	0.72 MPa (105 PSI)
Cut-Out Pressure	0.93 MPa (135 PSI)
Number of Outlets	1
Performance	34.0 L/min
Noise Level	68 dB(A)
Dimensions (L x W x H)	302x434x382 mm
Net weight	10.9kg (without battery)

**Standard Equipment:** Vacuum Pump Oil (Part no: AS00VP050M), Adapter


AVAILABLE VARIANTS

"Z" VARIANT

**AC001G Z**  
 TOOL ONLY (DOES NOT INCLUDE BATTERY / CHARGER)


DVP181
18V | LXT

Vacuum Pump



**Cordless vacuum pump for air purge during installation of room air conditioner (designed to purge large air conditioning systems)**

- Dual-stage compression method generate vacuum level much higher than Single-stage compression method
- 60 minutes long run time enough to complete most purging jobs achieved by using two BL1860B
- Battery guards minimize the possibility of battery damage even if the machine falls down.



Flow Rate	113 L/min
Ultimate vacuum	20 Pa
Motor speed	3,200 min <sup>-1</sup>
Oil Tank Capacity	300 mL
Inlet port	5/16", 3/8"
Dimensions (L x W x H)	383 x 193 x 210 mm
Net weight	6.9 kg (without battery)

**Standard Equipment:** Vacuum Pump Oil (Part no: AS00VP050M), Adapter

**Optional Accessories:** Vacuum Hose (AS0A1154MK)  
 Vacuum Pump Valve with vacuum gauge (AS0VP085MK)  
 Shoulder bag (199486-4)

AVAILABLE VARIANTS

"Z" VARIANT

**DVP181 ZK**  
 TOOL ONLY (WITH CARRY CASE) (DOES NOT INCLUDE BATTERY / CHARGER)