CORDLESS	DHS680 165mm (6-1	Acc Pg. A134-156			
	18V LXT - Lithium-io	n Cordless Circular Sa	w		
	51857	-	TAN		
FIXING / FASTENING	BL				
DRILLING / PACT DRILLING		hless motor provides	higher		
PACI DRILLING	power and more wo				
	 Compact and lightweight 	5			
	 Automatic speed control 	: Automatically changes the	cutting speed according to		
	load condition for an opti	imum operation.			
ETE DRILLING /	 Blower function blows sa 	wdust off the cut line ahead	for a better cutting view		
DEMOLITION	• Twin LED Job light.		for a better cutting view.		
DEMOLITION	• Twin LED Job light. Specifications:-		for a setter cutaing view.		
CUTTING	Specifications:-		2		
CUTTING TE/ MASONRY/			2-1/4")		
CUTTING	Specifications:- Max cutting capacity	at 0 degrees : 57mm (at 45 degrees : 41mm at 50 degrees : 37mm	2-1/4") (1-5/8")		
CUTTING TE/ MASONRY/	Specifications:- Max cutting capacity Blade diameter	at 0 degrees : 57mm (at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2 ")	2-1/4") (1-5/8")		
CUTTING TE/ MASONRY/	Specifications:- Max cutting capacity Blade diameter No load speed (rpm)	at 0 degrees : 57mm (at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2") 5,000	2-1/4") (1-5/8") (1-7/16")		
CUTTING TE/ MASONRY/	Specifications:- Max cutting capacity Blade diameter	at 0 degrees : 57mm (at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2") 5,000	2-1/4") (1-5/8")		
CUTTING TE/ MASONRY/ METAL]	Specifications:- Max cutting capacity Blade diameter No load speed (rpm) Dimensions (L x W x H)	at 0 degrees : 57mm () at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2") 5,000 350x170x238mm (13- 3.1kg (6.8lbs)	2-1/4") (1-5/8") (1-7/16")		
CUTTING TE/ MASONRY/ METAL]	Specifications:- Max cutting capacity Blade diameter No load speed (rpm) Dimensions (L x W x H) Net weight	at 0 degrees : 57mm () at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2") 5,000 350x170x238mm (13- 3.1kg (6.8lbs)	2-1/4") (1-5/8") (1-7/16")		
CUTTING TE/ MASONRY/ METAL]	Specifications:- Max cutting capacity Blade diameter No load speed (rpm) Dimensions (L x W x H) Net weight	at 0 degrees : 57mm () at 45 degrees : 41mm at 50 degrees : 37mm 165mm (6-1/2 ") 5,000 350x170x238mm (13- 3.1kg (6.8lbs) rench, Rip fence, Dust nozzle.	2-1/4") (1-5/8") (1-7/16")		

18V LXT - L	.ithiun	n-ion (Cordle	ess S	lide Co	ompou	nd Miter S	aw
AND								
High Powe	r but (Compa	act					
Double slidi								
	0							
 Soft elastom 	ier carryi	ng grip	provide	es easy	job site	e portabil	ity.	
e a de act								
Specificatio	ns:-	(Ŕ				
Max cutting c	anacity		_	t 0 dog	rooc: 52 x	(200mm (2-1/16" x 11-3/4	1")
Max cutting to	apacity						(1" x 11-3/4")	+)
Blade diamete					(7-1/2")	x 300mm	(1 X 11-3/4)	
Bore				0mm	(7-172)			
No load speed	(rnm)			.200				
Dimensions (L				·	0 x 454m			
Net weight	A W A II)			2.7kg	0 X 43411			
	pinent.	vertical v	ISC, JUCK	etwiei		guiai Nuie,	Dust bay, Holu	ei set.
Accessorie TCT Saw Blac Size (mm)		LS713 / Kerf (mm)	DLS71 Rake	4 Teeth	Wood	Aluminum	Part N	0.
TCT Saw Blac	de for D Bore (mm)	Kerf (mm)	Rake	Teeth		Aluminum		
Accessorie TCT Saw Blac	de for D Bore	Kerf			Wood	Aluminum	Part N A-86	
Accessorie TCT Saw Blac Size (mm)	de for D Bore (mm)	Kerf (mm)	Rake	Teeth 72	~	Aluminum		
Accessorie TCT Saw Blac Size (mm)	de for D Bore (mm)	Kerf (mm)	Rake	Teeth 72	~	Aluminum		

SANDING / POLISHING

[C

SAWING	DLS600 165 mm (6-	-1/2")								Acc Pg.	A134-156
	18V LXT - Lithium-io	on Cordless Compo	ound Miter Saw								
ROUTERING / PLANING	ETIST Landourrace	nakita Pakita	7	High A Excelle			bil	ity			
CLEANING	High accuracy + Lig • Suitable for Cutting Bas					Ń	Inkit	L	(Prakage a	
HEAT GUN / LASERS	Compact and lightweight Specifications:-	5			mankites and		-				
	Blade Diameter Miter Angle	165 mm (6-1/2" 52° L / 52° R)	2		-	_	6	18		1/1/
PNEUMATIC TOOLS	Bevel Angle Max Cutting Capacity No Load Speed (RPM) Dimensions (L x W x H)	46° L / 46° R 90° Miter: 46 x 5,000 340x400x440 m		Accessories							
	Net weight Standard Equipment: Vertic	6.6 kg	ulas Dula	TCT Saw Blade	for DLS60	D					
GARDEN TOOLS	Standard Equipment: Veru	ai vise, nex wrench, mang	ular kule	Size (mm)	Plate (mm)	Kerf (mm)	Rake	Wood	Aluminum	Туре	Part No.
		AVAILABLE VARIANTS		165 x 20 x 64T	1.4	1.9	10	\checkmark		-	B-56487
	5.0Ah	3.0Ah	"Z" VARIANT	165 x 20 x 60T	1.2	1.8	5		\checkmark	-	B-56530
GENERATORS			DLS600 Z TOOL ONLY (DOES NOT INCLUDE BATTERY / CHARGER OR CARRY CASE)	165 x 20 x 60T	1.35	1.85	10	\checkmark		<i>Sefficut</i>	B-69892