



- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS

FS2700
Acc Pg. A024-031 **419**

Screwdriver

6 Stage torque adjustment for a wide range of applications.



- Best possible tool body for screwdriving.
- Easy to bring pressure in line with center of driving bit axis.
- Bit holder is provided.
- LED job light convenient for operation in dark job sites.
- Durable belt clip.

Specifications:-

Continuous rating Input	570W
Capacity	Hex screw : 6mm (1/4") Drywall screw : 6mm (1/4") Self drilling screw : 6mm (1/4")
Max Fastening Torque	Hard : 8-32 N.m
Driving shank (Hex)	6.35mm (1/4")
No load speed (rpm)	0-2,500
Dimensions (L x W x H)	301 x 70 x 207mm (11-7/8" x 2-3/4" x 8-1/8")
Net weight	1.8kg (4.0lbs)
Power supply cord	2.5m (8.2ft)

6842
Acc Pg. 031 **411**

Auto Feed Screwdriver

Drives screws quickly with very little effort.

- Offers a more rigid aluminum casing with a stopper base.
- Anti tilt device to prevent the screws from swaying.
- More Reliable Casing Attachment.
- New Silent Clutch, ensures high operation efficiency with direct drive transmission in reverse rotation.



Specifications:-

Continuous rating Input	470W
Capacity	Drywall screw : 4x25 - 55mm (5/32"x1" - 2-3/16")
Bit size	Hex Shank : 6.35mm (1/4")
No load speed (rpm)	4,700
Dimensions (L x W x H)	400x75x243mm (15-3/4"x2-15/16"x9-9/16")
Net weight	2.0kg (4.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Phillips bit, Belt clip, Thumb screw

TD0101
Acc Pg. A024 **411**

Impact Driver

Compact design for perfect handling.

- Externally accessible carbon brush.
- No harm to the wrist when a screw is seated.
- Enables to drive screws even without pre-drilling pilot holes.



Specifications:-

Continuous rating Input	230W
Capacity	Machine screw : M4 - M8 (5/32" - 5/16") Standard bolt : M5 - M14 (3/16" - 9/16") High tensile bolt : M5 - M10 (3/16" - 3/8") Coarse thread (in length): 22 - 90mm (7/8" - 3-1/2")
Driving shank (Hex)	6.35mm (1/4")
Impacts per minute (ipm)	0-3,200
No load speed (rpm)	0-3,600
Max. fastening torque	100N.m (885in.lbs)
Dimensions (L x W x H)	184 x 67 x 192mm (7-1/4" x 2-5/8" x 7-9/16")
Net weight	0.99kg (2.2lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Phillips bit.

6904VH 12.7mm (1/2")
Acc Pg. A032-036 **415**

Impact Wrench

Versatile impact wrench for fastening nuts, bolts, and even lag screws.

- 2 speed selection with variable speed in both ranges.
- Light weight design for comfort and control.
- Rugged housing with rubber bumper for long tool life.
- Optional bit adapter for driving wood bits.

Specifications:-

Continuous rating Input	360W
Capacity	Standard bolt: M10 - M16 (3/8" - 5/8") High tensile bolt: M10 - M12 (3/8" - 1/2") Square drive : 12.7mm (1/2")
Impacts per minute	Hi : 0-3,000ipm / Lo : 0-2,500ipm
No load speed	Hi : 0-2,400rpm / Lo : 0-2,100rpm
Max. fastening torque	Hi : 196N.m (145ft.lbs) Lo : 147N.m (109ft.lbs)
Overall length	265mm (10-3/8")
Net weight	2.5kg (4.0lbs)

Standard Equipment: Sockets 3.