

CORDLESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CONCRETE DRILLING / DEMOLITION

CUTTING [CONCRETE/ MASONRY/ METAL]

MULTI TOOL

GRINDING

SANDING / POLISHING

SAWING

ROUTERING / PLANING

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS

Drywall Screwdrivers

Acc Pg. A024-031 419



	FS4300	FS2300	FS6300
	Drywall Screwdriver	Drywall Screwdriver	Drywall Screwdriver
Continuous rating Input	570W	570W	570W
Capacity	Drywall screw : 5mm (3/16") Self drilling screw : 6mm (1/4")	Drywall screw : 5mm (3/16") Self drilling screw : 6mm (1/4")	Drywall screw : 4mm (5/32") -
Max Fastening Torque	Hard : 16Nm	Hard : 25Nm	Hard : 11Nm
Driving shank (Hex)	6.35mm (1/4")	6.35mm (1/4")	6.35mm (1/4")
No load speed (rpm)	0-4,000	0-2,500	0-6,000
Dimensions (L x W x H)	279 x 65 x 207mm (11" x 2-9/16" x 8-1/8")	290 x 70 x 207mm (11-3/8" x 2-3/4" x 8-1/8")	279 x 65 x 207mm (11" x 2-9/16" x 8-1/8")
Net weight	1.4kg (3.1lbs)	1.6kg (3.5lbs)	1.4kg (3.1lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)

Silent clutch for quiet operation

- Best possible tool body for screwdriving.
- Easy to bring pressure in line with center of driving bit axis.
- Bit holder and locator holder are provided.
- One touch locator, Durable belt clip.



ONLY FOR FS2300 | FS6300

Standard Equipment: Phillips Insert Bit (2pcs), Magnetic Bit Holder



6821

Acc Pg. A024-031 419

Drywall Screwdriver



Powerful Makita motor for high speed performance.

- In-line design handle for maximum power thrust.
- Low noise level for quieter operation.
- Adjustable depth locator for consistent screw depth.
- Large variable speed trigger.

Specifications:-



Continuous rating input	570 W
Capacities	Drywall screw : 5 mm (3/16") Self drilling screw : 6 mm (1/4") Driving Shank (Hex) : 6 mm (1/4")
No load speed	0 - 4,000 rpm
Overall length	273 mm (10-3/4")
Net weight	1.3 kg (2.9 lbs)
Power supply cord	2.0 m (6.6 ft.)

Standard Equipment: Phillips Insert Bit (2pcs), Magnetic Bit Holder

FS2500

Acc Pg. A024-031 419

Screwdriver



Best possible tool body for screwdriving.

- Easy connect bit allows for quick bit change without using pliers.
- One touch locator, durable belt clip.
- A fully adjustable nose piece
- Can be used with self-drilling Tek screws
- Ideal for for roofing, façade, cladding and warehousing works

Specifications:-



Continuous rating Input	570W
Capacity	Drywall screw : 5mm (3/16") Self drilling screw : 6mm (1/4")
Max Fastening Torque	29 N.m
Driving shank (Hex)	6.35mm (1/4")
No load speed (rpm)	0-2,500
Dimensions (L x W x H)	280 x 70 x 207mm (11" x 2-3/4" x 8-1/8")
Net weight	1.5kg (3.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Magnetic Socket Bit