





Angle Grinder - 1,050W (Large Trigger Switch) (Finger Trigger Switch)

Acc Pg. A097-123 **303**

	GA5011 125mm (5")	GA5010 125mm (5")	GA6010 150mm (6")
Continuous rating input	1,050W	1,050W	1,050W
Wheel Diameter	125 mm (5")	125 mm (5")	150 mm (6")
No Load Speed (RPM)	12,000	12,000	10,000
Vibration Level	Surface Grinding: 13.5 m/s ²	Surface Grinding: 9.5 m/s ² Disc Sanding: 2.5 m/s ² or less	Surface Grinding: 9.5 m/s ² Disc Sanding: 2.5 m/s ²
Sound Pressure Level	90 dB(A)	89 dB(A)	90 dB(A)
Sound Power Level	101 dB(A)	100 dB(A)	101 dB(A)
Dimensions (L x W x H)	384x139x113 mm	356x139x112 mm	356x169x112 mm
Net weight	2.6kg	2.6 kg	2.7 kg
Power supply cord	2.5 m	2.5 m	2.5 m



High durability

- Large trigger switch (GA5011)
- Switch with easy-to-operate single-finger trigger. (GA5010, GA6010)
- Lightweight at only 2.6kg.
- High dust-proof construction.
- Ergonomically designed handle with rubberized grip provides more control and comfort.

Standard Equipment: Lock Nut Wrench, Grip.

CORDLESS

FIXING /
FASTENINGDRILLING /
IMPACT DRILLINGCONCRETE DRILLING /
DEMOLITIONCUTTING
[CONCRETE/ MASONRY/
METAL]

MULTI TOOL

GRINDING

SANDING /
POLISHING

SAWING

ROUTERING /
PLANING


CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS





GENERATORS




Angle Grinder - 1,100W (Slide Switch) (SJS)

Acc Pg. A097-123 **325**

	9563HZ 100mm (4")	9565HZ 125mm (5")
Continuous rating input	1,100W	1,100W
Wheel Diameter	100 mm (4")	125 mm (5")
No Load Speed (RPM)	12,000	12,000
Vibration Level	Surface Grinding: 5.5 m/s ² Anti-Vibration Side Grip: 7.5 m/s ² Disc Sanding: 2.5 m/s ² or less	Surface Grinding with Anti-Vibration Side Grip: 7.5 m/s ² Disc Sanding: 2.5 m/s ² or less
Sound Pressure Level	85 dB(A)	84 dB(A)
Sound Power Level	96 dB(A)	95 dB(A)
Dimensions (L x W x H)	299x120x103 mm (11-3/4"x4-3/4"x4")	299x139x103 mm (11-3/4"x5-1/2"x4")
Net weight	2.1 kg (4.6 lbs.)	2.3 kg (5.1 lbs)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)









High 1,100W power anti-dust motor.

- Super Joint System absorbs shock caused by accidental wheel lock and protects gears.
- Housing shape is easy to grip because of internal Brush Holders.
- Labyrinth construction seals motor and bearings from contamination.





Standard Equipment: Lock Nut Wrench, Grip.




Angle Grinder - 1,100W (Slide Switch) (SJS II)

Acc Pg. A097-123 **325**

	GA4040Z 100mm (4")	GA4540Z 115mm (4-1/2")	GA5040Z 125mm (5")
Continuous rating input	1,100W	1,100W	1,100W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
No Load Speed (RPM)	11,000	11,000	11,000
Vibration Level	Surface Grinding : 5.5 m/s ² Disc Sanding with Anti-Vibration Side Grip: 2.5 m/s ² or less	Surface Grinding : 6.0 m/s ² Disc Sanding with Anti-Vibration Side Grip: 2.5 m/s ² or less	Surface Grinding : 6.0 m/s ² Disc Sanding with Anti-Vibration Side Grip: 2.5 m/s ² or less
Sound Pressure Level	86 dB(A)	86 dB(A)	86 dB(A)
Sound Power Level	97 dB(A)	97 dB(A)	97 dB(A)
Dimensions (L x W x H)	303x117x111 mm (11-7/8"x4-5/8"x4-3/8")	303x130x116 mm (11-7/8"x5-1/8"x4-9/16")	303x140x116 mm (11-7/8"x5-1/2"x4-9/16")
Net weight	2.2 - kg (4.9 lbs)	2.3 kg (5.2 lbs)	2.4 (5.2 lbs)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



"Super Joint System II" developed for effective vibration absorption.

- Re-designed durable gear housing.
- Ergonomically best possible barrel grip.

Standard Equipment: Lock Nut Wrench, Grip.