









Angle Grinder - 1,650W-2,000W (Anti Restart) (Large Trigger Switch) Acc Pg. A097-123 204 Miles				
	GA7050R 180mm (7")	GA9050R 230mm (9")		
Continuous rating input	127V : 1,650 W	127V:1,650 W		
	220 - 240V : 2,000 W	220 - 240V : 2,000 W		
Wheel Diameter	180 mm (7")	230 mm (9")		
No Load Speed (RPM)	8,500	6,600		
Vibration Level	Surface Grinding: 6.5 m/s ²	Surface Grinding: 5.5 m/s ²		
	Disc Sanding: 4.0 m/s²	Disc Sanding: 2.5 m/s ²		
Sound Pressure Level	94 dB(A)	94 dB(A)		
Sound Power Level	105 dB(A)	105 dB(A)		
Dimensions	455x200x132 mm	455x250x132 mm		
(L x W x H)	(17-7/8"x7-7/8"x5-3/16")	(17-7/8"x9-7/8"x5-3/16")		
Net weight	4.6 kg (10.3 lbs.)	4.8 (10.6 lbs)		
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)		

Most compact in its class

- Small and rotatable gear housing.
- Large trigger switch.
- Light weight.

Standard Equipment: Lock Nut Wrench, Grip.

CORDI ESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CONCRETE DRILLING / DEMOLITION

CUTTING [CONCRETE/ MASONRY/



GA7020 180mm (7") Continuous rating input 2,200W Wheel Diameter No Load Speed (RPM) 180 mm (7") 8,500 Surface Grinding: 8.0 m/s² Vibration Level Disc Sanding: 2.5 m/s² **Sound Pressure Level** 89 dB(A) 100 dB(A) Sound Power Level Dimensions 473x200x140 mm (18-5/8"x7-7/8"x5-1/2") (L x W x H) Net weight 5.56 kg (12.26 lbs) 2.5 m (8.2 ft) Power supply cord **Outstanding durability** Increased heat resistance. • Superior anti-dust structure. • Machined bevel gear for strength.

Angle Grinder - 2,200W (Large Trigger Switch)

GA9020 230mm (9") 2,200W 230 mm (9") 6,600 Surface Grinding: 5.5 m/s² Disc Sanding: 2.5 m/s² or less 89 dB(A) 100 dB(A) 473x249x140 mm (18-5/8"x9-3/4"x5-1/2") 5.76 kg (12.7 lbs) 2.5 m (8.2 ft)

- Soft grip for more comfort and control.
- Gear housing can be positioned at every 90 degrees.

Standard Equipment: Lock Nut Wrench, Grip.

Acc Pg. A097-123 204 MM MULTI TOOL

GRINDING

SANDING / POLISHING

SAWING

ROUTERING / PLANING

D-SHAPE HANDLE
2,200W



	GA7062 180mm (7")	GA9062 230mm (9")	
Continuous rating input	2,200W	2,200W	
Wheel Diameter	180 mm (7")	230 mm (9")	
No Load Speed (RPM)	8,500	6,600	
Vibration Level	Surface Grinding: 7.5 m/s ²	Surface Grinding : 6.0 m/s ²	
	Disc Sanding : 2.5 m/s ²	Disc Sanding : 2.5 m/s ² or less	
Sound Pressure Level	91 dB(A)	91 dB(A)	
Sound Power Level	102 dB(A)	102 dB(A)	
Dimensions	450x200x144 mm	450x250x144 mm	
(L x W x H)	(17-3/4"x7-7/8"x5-5/8")	(17-3/4"x9-7/8"x5-5/8")	
Net weight	5.51 kg (12.2 lbs)	5.61 kg (12.4 lbs)	
Power supply cord	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)	

- Improvement of armature, commutator, carbon brush life, switch section, shaft lock pin, new brush holder and rigid motor housing.
- D-shape Handle protects user's hand from materials
- Easy to grip handle with anti-slip shape and comfortable side grip for better balance
- Compact and light weight

Standard Equipment: Lock Nut Wrench, Grip.

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS