

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING (CONCRETE/ MASONRY/ METAL)



Angle Grinder - 2,200W (Large Trigger Switch) (SJS II) Acc Pg. A097-123 **218**

	GA7063 180mm (7")	GA9063 230mm (9")
Continuous rating input	2,200W	2,200W
Wheel Diameter	180 mm (7")	230 mm (9")
No Load Speed (RPM)	8,500	6,600
Vibration Level	Surface Grinding: 6.5 m/s ² Disc Sanding : 2.5 m/s ² or less	Surface Grinding with : 5.5 m/s ² Disc Sanding : 2.5 m/s ² or less
Sound Pressure Level	91 dB(A)	91 dB(A)
Sound Power Level	102 dB(A)	102 dB(A)
Dimensions (L x W x H)	450x200x145 mm (17-3/4"x7-7/8"x5-3/4")	450x250x145 mm (17-3/4"x9-7/8"x5-3/4")
Net weight	5.64 - kg (12.4 lbs)	5.75 kg (12.7 lbs)
Power supply cord	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)

High durability and Superior usability D shape Handle grinders with "Super Joint System II" developed for effective vibration absorption

- Improvement of armature, commutator, carbon brush life, switch section, shaft lock pin, new brush holder and rigid motor housing.
- D-shape Handle protects user's hand from materials
- Easy to grip handle with anti-slip shape and comfortable side grip for better balance
- Compact and light weight

Standard Equipment: Lock Nut Wrench, Grip.

- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING



Angle Grinder - 2,200W - 2,400W (Large Trigger Switch) Acc Pg. A097-123 **204**

	GA7030 180mm (7")	GA9030 230mm (9")
Continuous rating input	2,400W (220V) / 2,200W (127V)	2,400W (220V) / 2,200W (127V)
Wheel Diameter	180 mm (7")	230 mm (9")
No Load Speed (RPM)	8,500	6,600
Vibration Level	Surface Grinding: 6.5 m/s ² Disc Sanding: 2.5 m/s ²	Surface Grinding: 6.5 m/s ² Disc Sanding: 2.5 m/s ² or less
Sound Pressure Level	89 dB(A)	90 dB(A)
Sound Power Level	100 dB(A)	101 dB(A)
Dimensions (L x W x H)	511x200x140 mm (20-1/8"x7-7/8"x5-1/2")	503x250x140 mm (19-3/4"x9-7/8"x5-1/2")
Net weight	6.06 kg (13.36 lbs)	6.26 kg (13.8 lbs)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)

Heavy duty motor with 2,200W - 2,400W continuous rating input.

- Outstanding durability. Superior anti-dust Structure, Machined bevel gear.Increased heat resistance.
- Low vibration rear handle with soft grip for more comfort and control.
- Rotatable rear handle can be positioned to suit most cutting & grinding operations.
- Protects work piece from scratches large rubber tool rest.
- Gear housing can be positioned at every 90 degrees.

Standard Equipment: Lock Nut Wrench, Grip.

- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS



Angle Grinder - 2,600W (Large Trigger Switch) Acc Pg. A097-123 **204**

	GA7040S 180mm (7")	GA9040S 230mm (9")
Continuous rating input	2,600W	2,600W
Wheel Diameter	180 mm (7")	230 mm (9")
No Load Speed (RPM)	8,500	6,600
Vibration Level	Surface Grinding: 7.5 m/s ² Disc Sanding: 2.5 m/s ²	Surface Grinding: 5.5 m/s ² Disc Sanding: 2.5 m/s ² or less
Sound Pressure Level	90 dB(A)	90 dB(A)
Sound Power Level	101 dB(A)	101 dB(A)
Dimensions (L x W x H)	511x200x140 mm (20-1/8"x7-7/8"x5-1/2")	503x250x140 mm (19-3/4"x9-7/8"x5-1/2")
Net weight	6.45 kg (14.2 lbs)	6.65 - 8.94 kg (14.7 lbs)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)

Heavy duty motor with 2,600W continuous rating input.

- Outstanding durability. Superior anti-dust Structure, Machined bevel gear.Increased heat resistance.
- Low vibration rear handle with soft grip for more comfort and control.
- Rotatable rear handle can be positioned to suit most cutting & grinding operations.
- Protects work piece from scratches large rubber tool rest.
- Gear housing can be positioned at every 90 degrees.

Standard Equipment: Lock Nut Wrench, Grip.