


**906** 6mm (1/4") Acc Pg. A118-119 **64** 

**Die Grinder**

**240W MOTOR**


**Light weight for controlled Grinding operations.**

- Ideal for light, precision grinding.
- Palm-sized grinder for multi-applications.
- High speed (25,000rpm) for maximum production.



**Specifications:-** 

|                                |                      |
|--------------------------------|----------------------|
| <b>Continuous rating Input</b> | 240W                 |
| <b>Capacity</b>                | Collet : 6mm or 1/4" |
| <b>No load speed</b>           | 25,000rpm            |
| <b>Overall length</b>          | 283mm (11-1/8")      |
| <b>Net weight</b>              | 0.94kg (2.1lbs)      |
| <b>Power supply cord</b>       | 2.5m (8.2ft)         |

**Standard Equipment:** Wrench (2pcs.)

**GD0603** 6mm (1/4") Acc Pg. A118-119 **64** 

**Die Grinder**





**NEW PRODUCT**

**240W MOTOR**

**Compact design with small diameter barrel**

- Power and speed in a compact size, and features motor-protection features for longer tool life
- Contoured neck grip provides a secondary hand position for increased maneuverability
- Round-shaped collet nut is designed to help prevent damage/scratches to workpiece
- Can be gripped close to the stone for steadier work.

**Specifications:-** 

|                                      |                  |
|--------------------------------------|------------------|
| <b>Continuous rating Input</b>       | 240W             |
| <b>Collet Capacity</b>               | 6 mm or 1/4"     |
| <b>Max Wheel Diameter</b>            | 19 mm (3/4")     |
| <b>No Load Speed (RPM)</b>           | 28,000           |
| <b>Diameter of grip</b>              | 65 mm            |
| <b>Circumference of Grip Portion</b> | 203 mm           |
| <b>Dimensions (L x W x H)</b>        | 289 x 64 x 67 mm |
| <b>Net weight</b>                    | 0.98 kg          |
| <b>Power supply cord</b>             | 2.5 m            |

**Standard Equipment:** Spanner

CORDLESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CONCRETE DRILLING / DEMOLITION

CUTTING [CONCRETE/ MASONRY/ METAL]

MULTI TOOL

GRINDING

SANDING / POLISHING

SAWING

ROUTERING / PLANING

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS

**GD0600** 6mm (1/4") Acc Pg. A118-119 **325** 

**Die Grinder**




**400W MOTOR**

**Small-circumference housing for easy handling.**

- Anti-slip rubber cover for easy handling.
- Round-shaped collet nut reduces the possibility of damages/ scratches to workpiece.
- Vent slots designed to direct the exhaust air stream towards the opposite side of the operator.
- High heat resistance.
- Operate paddle type switch.

**Specifications:-** 

|                                |                              |
|--------------------------------|------------------------------|
| <b>Continuous rating Input</b> | 400W                         |
| <b>Capacity</b>                | Collet : 3.6mm or 1/8", 1/4" |
| <b>Wheel dia.</b>              | 38mm (2-1/2")                |
| <b>No load speed</b>           | 25,000rpm                    |
| <b>Dimensions</b>              | 358mm x 82mm x 82mm          |
| <b>(L x W x H)</b>             | (14-1/8" x 3-1/4" x 3-1/4")  |
| <b>Net weight</b>              | 1.7kg (3.7lbs)               |
| <b>Power supply cord</b>       | 2.5m (8.2ft)                 |

**Standard Equipment:** Wrench (2pcs.)

**GD0602** 6mm (1/4") Acc Pg. A118-119 **325** 

**Die Grinder**




**400W MOTOR**

**Compact body with short nose.**

- Anti-slip rubber cover for easy handling.
- Round-shaped collet nut reduces the possibility of damages/scratches to the workpiece.
- Switch lever conveniently located for one hand operation.
- Vent slots designed to direct the exhaust air stream towards the opposite side of the operator.

**Specifications:-** 

|                                |                             |
|--------------------------------|-----------------------------|
| <b>Continuous rating Input</b> | 400W                        |
| <b>Capacity</b>                | Collet : 6mm or 1/4"        |
| <b>Wheel dia.</b>              | 38mm (1-1/2")               |
| <b>No load speed (rpm)</b>     | 25,000                      |
| <b>Dimensions</b>              | 264 x 82 x 82mm             |
| <b>(L x W x H)</b>             | (10-3/8" x 3-1/4" x 3-1/4") |
| <b>Net weight</b>              | 1.4kg (3.2lbs)              |
| <b>Power supply cord</b>       | 2.5m (8.2ft)                |

**Standard Equipment:** Wrench (2pcs.)