

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS

**GD0800C** 8mm (1/4")
Acc Pg. A118-119 **318**

**Die Grinder**

High speed for mounted points - Max wheel point 25mm

750W  
MOTOR

**High-speed die grinder with max. 8mm collet capacity.**

- Ergonomically designed slim body for grinding in tight spots.
- Super Joint System absorbs shock caused by accidental wheel lock and protects gears.
- Internal labyrinth construction seals motor and bearings from contamination.

**Specifications:-**

|                                |   |
|--------------------------------|---|
| <b>Continuous rating Input</b> | 750W                                    |
| <b>Capacity</b>                | Collet : 3,6,8mm or 1/8",1/4"           |
| <b>Max wheel point dia.</b>    | 25mm                                    |
| <b>No load speed</b>           | 7,000-28,000rpm                         |
| <b>Dimensions (L x W x H)</b>  | 371x75x75mm (14-5/8"x2-15/16"x2-15/16") |
| <b>Net weight</b>              | 1.7kg (3.7lbs)                          |
| <b>Power supply cord</b>       | 2.5m (8.2ft)                            |

**Standard Equipment:** Wrench (2pcs)

**GD0810C** 8mm (1/4")
Acc Pg. A118-119 **318**

**Die Grinder**

Low speed for flap discs - Max wheel point 50mm

750W  
MOTOR

**Low-speed die grinder with max. 8mm collet capacity.**

- Ergonomically designed slim body for grinding in tight spots.
- Super Joint System absorbs shock caused by accidental wheel lock and protects gears.
- Internal labyrinth construction seals motor and bearings from contamination.
- Ideal for grinding internal surfaces, removing paint etc. using with flap wheel discs.

**Specifications:-**

|                                |                               |
|--------------------------------|-------------------------------|
| <b>Continuous rating Input</b> | 750W                          |
| <b>Capacity</b>                | Collet : 3,6,8mm or 1/8",1/4" |
| <b>Max wheel point dia.</b>    | 50mm                          |
| <b>No load speed</b>           | 1,800-7,000rpm                |
| <b>Overall length</b>          | 371mm (14-5/8")               |
| <b>Net weight</b>              | 1.7kg (3.8lbs)                |
| <b>Power supply cord</b>       | 2.5m (ft)                     |

**Standard Equipment:** Wrench (2pcs)

**GD0801C** 8mm (1/4") (Paddle switch)
Acc Pg. A118-119 **318**

**Die Grinder**

Easy-to-operate paddle type on/off switch

750W  
MOTOR

**Easy-to-operate paddle type on/off switch**

- Ergonomically designed slim body for grinding in tight spots.
- Super Joint System absorbs shock caused by accidental wheel lock and protects gears.
- Side handle can be attached.

**Specifications:-**

|                                |                                       |
|--------------------------------|---------------------------------------|
| <b>Continuous rating input</b> | 750W                                  |
| <b>Capacity</b>                | Collet : 3,6,8mm or 1/8",1/4"         |
| <b>No load speed (rpm)</b>     | 7,000-29,000                          |
| <b>Dimensions (L x W x H)</b>  | 390x75x88mm (15-3/8"x2-15/16"x3-1/2") |
| <b>Net weight</b>              | 2.0kg (4.3lbs)                        |
| <b>Power supply cord</b>       | 2.5m (8.2ft)                          |

**Standard Equipment:** Wrench (2pcs)

**GD0811C** 8mm (1/4") (Paddle switch)
Acc Pg. A118-119 **318**

**Die Grinder**

Easy-to-operate paddle type on/off switch

750W  
MOTOR

**Easy-to-operate paddle type on/off switch**

- Ergonomically designed slim body for grinding in tight spots.
- Super Joint System absorbs shock caused by accidental wheel lock and protects gears.
- Internal labyrinth construction seals motor and bearings from contamination.
- Ideal for grinding internal surfaces, removing paint etc. using with flap wheel discs.

**Specifications:-**

|                                |                               |
|--------------------------------|-------------------------------|
| <b>Continuous rating input</b> | 750W                          |
| <b>Capacity</b>                | Collet : 3,6,8mm or 1/8",1/4" |
| <b>No load speed (rpm)</b>     | 1,800-7,000                   |
| <b>Overall length</b>          | 390mm (15-3/8")               |
| <b>Net weight</b>              | 2.0kg (4.4lbs)                |
| <b>Power supply cord</b>       | 2.5m (8.2ft)                  |

**Standard Equipment:** Wrench (2pcs)