HM1511 - Adapted for 30mm Hex shank

Acc Pg. A069-079 218

CORDLESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CUTTING

METAL]

MULTI TOOL

GRINDING

SANDING / POLISHING

CONCRETE DRILLING / DEMOLITION

[CONCRETE/ MASONRY/

Electric Breaker





Powerful 1,850 W motor delivers 48.9 J (EPTA) of impact energy to handle the most demanding applications

- Both drastically increased power and low vibration are achieved with minimum increase in tool size and weight
- Thanks to completely redesigned hammering mechanism and increased motor power as compared with HM1317C serie
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced and L.E.D. power light indicates switch failure or cord damage
- Rubberized ergonomic soft grip provides more comfort

- Easy-to-operate slide switch increases productivity and allows for continuous use
 Side handle swivels 360° for greater control

Specifications:-	
Continuous rating Input	1,850W
Impact Energy	EPTA (//8 Q I)

Continuous rating Input	1,850W
Impact Energy	EPTA (48.9 J)
Blows Per Minute (BPM)	1,300
Dimensions (L x W x H)	781 x 130 x 266 mm
Net weight	19.2 kg
Power supply cord	4.0 m

Standard Equipment: Side Handle. (Tool does not come with bit)



Power Scraper		18	SAWING
			ROUTERING /
3.9 JOULES	2 0		PLANING
Quick in removing tile	es / concrete scale	s / weld spatter /	
Employs SDS-Plus bit syste12 bit angle settings.		-	CLEANING
Lighter than the competing	, i i		
• Lowest-in-class vibration (10m/s2) ensures more c	omfort and control.	
Increased repairability of e	·		HEAT GUN / LA
Specifications:-			HEAT GUN / LA
Specifications:- Continuous rating Input	550W		HEAT GUN / LA
Specifications:- Continuous rating Input Impacts per minute	550W 0 - 3,200 ipm		HEAT GUN / LA
Specifications:- Continuous rating Input	550W		
Specifications:- Continuous rating Input Impacts per minute Sound pressure level	550W 0 - 3,200 ipm 83dB(A)		HEAT GUN / LA
Specifications:- Continuous rating Input Impacts per minute Sound pressure level Sound power level	550W 0 - 3,200 ipm 83dB(A) 94dB(A) 10m/s ²)3 mm (13-3/4″ x 4″ x 8″)	
Specifications:- Continuous rating Input Impacts per minute Sound pressure level Sound power level Vibration Dimensions (L x W x H)	550W 0 - 3,200 ipm 83dB(A) 94dB(A) 10m/s ²		
Specifications:- Continuous rating Input Impacts per minute Sound pressure level Sound power level Vibration	550W 0 - 3,200 ipm 83dB(A) 94dB(A) 10m/s ² 351mm x 102mm x 2 ⁱ		PNEUMATIC TO
Specifications:- Continuous rating Input Impacts per minute Sound pressure level Sound power level Vibration Dimensions (L x W x H) Net weight	550W 0 - 3,200 ipm 83dB(A) 94dB(A) 10m/s ² 351mm x 102mm x 2/ 3.4 kg (7.5 lbs)		PNEUMATIC TO
Specifications:- Continuous rating Input Impacts per minute Sound pressure level Sound power level Vibration Dimensions (L x W x H) Net weight	550W 0 - 3,200 ipm 83dB(A) 94dB(A) 10m/s ² 351mm x 102mm x 2/ 3.4 kg (7.5 lbs)		

Acc Pg. A069-079 106 HK0500 - Adapted for SDS-PLUS Shank Power Scraper 2.8 JOULES For scraping, chiseling and chipping. • Bit inserts easily; just slide sleeve down to remove. • 12 different bit angle settings. • One touch sliding chuck with dust protection.

Specifications:-



Continuous rating Input	550W		
Impacts per minute	2,000 – 3,500 ipm		
Sound pressure level	83dB(A)		
Sound power level	94dB(A)		
Overall length	468 mm (18-7/16")		
Net weight	3.2 kg (7.1 lbs)		
Power supply cord	5.0 m (16.4 ft)		
Standard Equipment: Scaling Chisel.			