

HM1213C - Adapted for SDS-MAX Shank Acc Pg. A069-079 **175** 

Demolition Hammer



25.5 JOULES
AVT SOFT NOLOAD
ANTI-VIBRATION TECHNOLOGY



AVT (Anti-Vibration Technology) ensures extra-low vibration performance.

- Suppression of motor speed during no-load reduces vibration of tool body.
- One touch sliding chuck for easy bit installation and removal.
- Electronic speed control for maximum performance.
- Bit can be set at 12 positions for convenience.
- LED lamp indicates when to replace carbon brush.

Specifications:- 

Continuous rating Input	1,510W
Impacts per minute	950-1,900 ipm
Sound pressure level	75dB(A)
Sound power level	95dB(A)
Vibration level	Chiseling: 8.0m/s ²
Dimensions (L x W x H)	576 x 149 x 265mm (22-3/4" x 5-7/8" x 10-3/8")
Net weight	10.8kg (23.6lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Bull Point, Bit Grease, Side Handle.

HM1214C - Adapted for SDS-MAX Shank Acc Pg. A069-079 **175** 

Demolition Hammer



26 JOULES
AVT SOFT NOLOAD
ANTI-VIBRATION TECHNOLOGY



Comfortable operation at hammering downward.

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance.
- Suppression of motor speed during no-load reduces vibration of tool body.
- Long size carbon brush for service life is extended.
- One touch sliding chuck for easy bit installation and removal.
- LED lamp indicates when to replace carbon brush.

Specifications:- 


Continuous rating Input	1,510W
Impacts per minute (ipm)	950-1,900
Sound pressure level	78dB(A)
Sound power level	98dB(A)
Vibration level	Chiseling: 8m/s ²
Dimensions (L x W x H)	700 x 129 x 265mm (27-1/2" x 5-1/8" x 10-3/8")
Net weight	12.3kg (27.1lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Bull Point, Bit Grease, Side Handle.

HM1306 Adapted for 30mm Hex Shank Acc Pg. A069-079 **204** 

Demolition Hammer

Oil Lubrication




28.8 JOULES



Chipping performance ensures minimum power loss even when bull point is kept pushed against concrete in chipping operation.

- High durability.
- Soft grip provides more control and less hand fatigue.
- Adjustable large side handle improves operator comfort and control.

Specifications:- 

Continuous rating Input	1,510W
Impacts per minute (ipm)	1,450
Dimensions (L x W x H)	652 x 121 x 231mm (25-3/4" x 4-3/4" x 9-1/8")
Net weight	15.1kg (33.3lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Bull Point, Wrench, Side Handle, Oil Supply 100mL

HM1307C Adapted for 30mm Hex Shank Acc Pg. A069-079 **175** 

Demolition Hammer



33.8 JOULES



High durability and excellent demolition performance.

- Electrical speed control for maximum performance.
- LED lamp indicates when to replace carbon brush.
- LED lamp is provided as a pilot lamp.

Specifications:- 

Continuous rating Input	1,510W
Impacts per minute (ipm)	730-1,450
Sound pressure level	81dB(A)
Sound power level	101dB(A)
Vibration level	Chiseling: 12.5m/s ²
Dimensions (L x W x H)	715 x 129 x 266mm (28-1/8" x 5-1/8" x 10-1/2")
Net weight	15.3kg (33.8lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Side Handle. (Tool does not come with bit)

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS