

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS

**HM1317C** - Adapted for 30mm Hex Shank Acc Pg. A069-079 175

**Demolition Hammer**

**33.8 JOULES** **AVT** **SOFT NO LOAD**  
ANTI VIBRATION TECHNOLOGY

**AVT (Anti-Vibration Technology) ensures extra-low vibration performance.**

- Suppression of motor speed during no-load reduces vibration of tool body.
- High durability and excellent demolition performance.
- Electrical speed control for maximum performance.
- LED lamp indicates when to replace carbon brush.
- LED lamp is provided as a pilot lamp.

**Specifications:-**

Continuous rating Input	1,510W
Impacts per minute	730-1,450 ipm
Sound pressure level	81dB(A)
Sound power level	101dB(A)
Vibration	Chiseling: 8.5m/s <sup>2</sup>
Dimensions (L x W x H)	715 x 129 x 266mm (28-1/8" x 5-1/8" x 10-1/2")
Net weight	17.0kg (37.5lbs)
Power supply cord	5.0m (16.4ft)

**Standard Equipment:** Side Handle. (Tool does not come with bit)

**HM1812** - Adapted for 28.6mm Hex Shank Acc Pg. A069-079

**Electric Breaker**

**72.8 JOULES**

**Highest-in-class demolition power with AVT (Anti-Vibration Technology)**

- Counter weight mechanism and vibration absorbing housing helps to reduce vibration.
- Suppression of motor speed during no-load reduces vibration of tool body when idling.
- Soft start for suppressing start-up reaction.
- Soft grip provides more control and less hand fatigue.

**The first electric breakers from Makita that are equipped with vibration absorbing housing providing a practical combination of high power and low vibration.**

**Soft grip**

**Highly durable switch**

**Improved repairability**

**Electronic control**

- Soft start
- LED light to indicate energization of electric circuit
- LED light to indicate the time to replace carbon brush

**Auto cut-off carbon brush**

**SOFT NO LOAD AVT**  
ANTI VIBRATION TECHNOLOGY

**Advance Vibration Control**

**Recessed hand hold**  
Helps you raise a machine upright for easy transport. Located on the both sides of the machine for convenience

**Vibration absorbing housing**  
Vibration absorbing spring (4 places)

The machine holding section is separated from the motor/transmission section

**Specifications:-**

Continuous rating Input	2,000W
Impact energy	71.4J
Impacts per minute (ipm)	870
Sound pressure level	95dB(A)
Sound power level	106dB(A)
Vibration level	14.0m/s <sup>2</sup>
Dimensions (L x W x H)	843x210x608mm (33-1/4"x8-1/4"x24")
Net weight	30.1kg (66.4lbs)
Power supply cord	5.0m (16.4ft)

**Standard Equipment:** Bull point, Hex wrench.

**HM1802** - Adapted for 28.6mm Hex Shank Acc Pg. A069-079

**Electric Breaker**

**71.4 JOULES**

**Highest-in-class demolition power.**

- Vibration absorbing housing helps to reduce vibration.
- Soft start for suppressing start-up reaction.
- Soft grip provides more control and less hand fatigue.
- Higher durability obtained by strengthening switch.
- Newly developed dust extraction attachment is available.

**Specifications:-**

Continuous rating Input	2,000W
Impact energy	71.4J
Impacts per minute (ipm)	870
Sound pressure level	95dB(A)
Sound power level	106dB(A)
Vibration level	14.0m/s <sup>2</sup>
Dimensions (L x W x H)	843x210x608mm (33-1/4"x8-1/4"x24")
Net weight	30.1kg (66.4lbs)
Power supply cord	5.0m (16.4ft)

**Standard Equipment:** Bull point, Hex wrench.