

**HR2810** 28mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **325** mm

**Combination Hammer**



**2.9** JOULES

**3 Operation Modes: Hammering, Hammering with Rotation and Rotation only.**

- Highest-in-class efficiency in both drilling and chipping.
- Compact L-shaped motor housing.
- One-touch sliding chuck enables easy bit changes.
- Ergonomically designed handle with rubberized grip provides more control and comfort.

**Specifications:-**

<b>Continuous rating input</b>	800W
<b>Capacity</b>	Concrete (with T.C.T. bit) : 28mm (1-1/8") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
<b>Impacts per minute (ipm)</b>	0-4,500
<b>No load speed (rpm)</b>	0-1,100
<b>Sound pressure level</b>	89dB(A)
<b>Sound power level</b>	100dB(A)
<b>Vibration level</b>	Chiseling: 15.5m/s <sup>2</sup> , Hammer drilling: 20m/s <sup>2</sup> Drilling: 2.5m/s <sup>2</sup>
<b>Dimensions (L x W x H)</b>	314x89x225mm (12-3/8"x3-1/2"x8-7/8")
<b>Net weight</b>	3.2kg (7.1lbs)
<b>Power supply cord</b>	2.5m (8.2ft)

**Standard Equipment:** Side Grip, Depth Gauge. (Tool does not come with bit)

**HR3011FCWJ** 30mm - SDS-PLUS Shank Acc Pg. A062-079 **350** mm

**Combination Hammer with dust extraction**



**NEW PRODUCT**

**3.9** JOULES **AVT** ANTI-VIBRATION TECHNOLOGY

**Superior drilling efficiency**

- The impact energy is drastically increased from that of Predecessor model by redesigned hammering mechanism
- Less bit wobbling achieved by 8mm longer bit guide portion
- Equipped with Anti Vibration Technology for low vibration with Anti-vibration side grip and Anti-vibration rear handle
- Dust Extraction System (DX10) with HEPA filter and Filter cleaning mechanism
- Dust collection is available for bits with an overall length of up to 265mm

**Specifications:-**

<b>Continuous rating Input</b>	1,050W
<b>Impact Energy</b>	EPTA-Procedure : 3.9 J
<b>Capacity</b>	Concrete (w/ TCT Bit): 30 mm (1-3/16") Concrete (w/ Diamond Core Bit): 80 mm (3-1/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 30 mm (1-3/16")
<b>Chuck Capacity</b>	1.5 - 13 mm (1/16 - 1/2")
<b>Blows Per Minute (BPM)</b>	0 - 4,500
<b>No Load Speed (RPM)</b>	0 - 840
<b>Dimensions (L x W x H)</b>	369 x 98 x 242 mm
<b>Net weight</b>	4.7 kg
<b>Power supply cord</b>	4.0 m

**Standard Equipment:** Side handle, Depth gauge (Tool does not comes with bit.)

**HR3012FCWJ** 30mm - SDS-PLUS Shank Acc Pg. A062-079 **350** mm

**Combination Hammer with dust extraction**



**NEW PRODUCT**

**3.9** JOULES **AVT** ANTI-VIBRATION TECHNOLOGY

With Quick change drill chuck

**Superior drilling efficiency**

- The impact energy is drastically increased from that of Predecessor model by redesigned hammering mechanism
- Less bit wobbling achieved by 8mm longer bit guide portion
- Equipped with Anti Vibration Technology for low vibration with Anti-vibration side grip and Anti-vibration rear handle
- Dust Extraction System (DX11) with HEPA filter and Filter cleaning mechanism
- Dust collection is available for bits with an overall length of up to 265mm

**Specifications:-**

<b>Continuous rating Input</b>	1,050W
<b>Impact Energy</b>	EPTA-Procedure: 3.9 J
<b>Capacity</b>	Concrete (w/ TCT Bit): 30 mm (1-3/16") Concrete (w/ Diamond Core Bit): 80 mm (3-1/8") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Wood (Self-Feed Bit): 32 mm (1-1/4") Masonry: 30 mm (1-3/16")
<b>Chuck Capacity</b>	1.5 - 13 mm
<b>Blows Per Minute (BPM)</b>	0 - 4,500
<b>No Load Speed (RPM)</b>	0 - 840
<b>Dimensions (L x W x H)</b>	386 x 98 x 242 mm
<b>Net weight</b>	4.7 kg
<b>Power supply cord</b>	4.0 m

**Standard Equipment:** Side handle, Depth gauge (Tool does not comes with bit.)

**HR3200C** 32mm - Adapted for SDS-PLUS Shank Acc Pg. A062-079 **350** mm

**Combination Hammer**



**5.5** JOULES

**Developed as the successor model of HR3000C**

- Simple Single-Lever Control to change the tool's operation mode.
- One-Touch sliding chuck for easy bit changes.
- Increased Repairability - with simplified wiring and bit holding mechanism.

**Specifications:-**

<b>Continuous rating input</b>	850W
<b>Capacity</b>	Concrete (with T.C.T. bit) : 32mm (1-1/4") Steel : 13mm (1/2") Wood : 32mm (1-1/4")
<b>Impacts per minute (ipm)</b>	1,650-3,300
<b>No load speed (rpm)</b>	315-630
<b>Sound pressure level</b>	89dB(A)
<b>Sound power level</b>	100dB(A)
<b>Vibration level</b>	Hammer drilling: 18m/s <sup>2</sup> , Chiseling: 12.5m/s <sup>2</sup> Drilling: 2.5m/s <sup>2</sup>
<b>Dimensions (L x W x H)</b>	398x108x239mm (15-5/8"x4-1/4"x9-3/8")
<b>Net weight</b>	4.8kg (10.5lbs)
<b>Power supply cord</b>	5.0m (16.4ft)

**Standard Equipment:** Side handle, Depth gauge, Bit grease, Plastic carrying case, Cleaning cloth (Tool does not comes with bit.)

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLIION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS