

CORDLESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CONCRETE DRILLING / DEMOLITION

CUTTING [CONCRETE/ MASONRY/ METAL]

MULTI TOOL

GRINDING

SANDING / POLISHING

SAWING

ROUTERING / PLANING

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS

HR4030C 40mm - Adapted for Hex Shank Acc Pg. A067-079 **350** 

Rotary Hammer



Make tough jobs easier with electronic control features and compact design. (Hex Shank type)

- No hammering while idling.
- When drill bit hits against reinforcements, torque limiter operates to stop.
- Aluminum housing provides high quality and toughness.
- Auto cut-out carbon brush.
- Electronic variable speed control dial enables to select speed to job.

Specifications:- 

Continuous rating input	1,100W
Capacity	Concrete (with T.C.T. bit) : 40mm (1-9/16") Concrete (with Core bit) : 118mm (4-5/8")
Impacts per minute (ipm)	1,300 - 2,600
No load speed (rpm)	230 - 460
Sound pressure level	92dB(A)
Sound power level	103dB(A)
Vibration level	9m/s ²
Dimensions (L x W x H)	413x107x247mm (16-1/4"x4-1/4"x9-3/4")
Net weight	6.9kg (15.2lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Depth Gauge, Side Grip (Tool does not come with bit.)

HR4501C 45mm - Adapted for SDS-MAX Shank Acc Pg. A065-079 **175** 

Rotary Hammer



High performance and durability.

- 2 operation modes - hammering and hammering with rotation.
- Selectable two on/off switches on demolition mode.
- One-Touch Sliding Chuck enables easy bit change.
- Ergonomically designed handle with rubberized grip provides more control and comfort.

Specifications:- 

Continuous rating input	1,350W
Capacity	Concrete (with T.C.T. bit) : 45mm (1-3/4") Concrete (with Core bit) : 125mm (5")
Impacts per minute (ipm)	1,250 - 2,750
No load speed (rpm)	130 - 280
Sound pressure level	94dB(A)
Sound power level	105dB(A)
Vibration level	Hammer drilling: 16m/s ² / Chiseling: 12.5m/s ²
Dimensions (L x W x H)	458x121x288mm (18"x4-3/4"x11-3/8")
Net weight	8.2kg (18.1lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Side Handle(D), Side Grip, Depth Gauge, Grease Vessel (Tool does not come with bit.)

HR4511C 45mm - Adapted for SDS-MAX Shank Acc Pg. A065-079 **175** 

Rotary Hammer



High performance and low vibration. (with Vibration absorbing grip)

- 2 operation modes - hammering and hammering with rotation.
- AVT (Anti-Vibration Technology) Active Dynamic Vibration Absorber ensures extra-low vibration performance.
- One-Touch Sliding Chuck enables easy bit change.
- Ergonomically designed handle with rubberized grip provides more control and comfort.

Specifications:- 

Continuous rating input	1,350W
Capacity	Concrete (with T.C.T. bit) : 45mm (1-3/4") Concrete (with Core bit) : 125mm (5")
Impacts per minute (ipm)	1,250 - 2,750
No load speed (rpm)	130 - 280
Sound pressure level	94dB(A)
Sound power level	105dB(A)
Vibration level	Hammer drilling: 7.5m/s ² / Chiseling: 7.5m/s ²
Dimensions (L x W x H)	458x136x288mm (18"x5-3/8"x11-3/8")
Net weight	8.5kg (18.7lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Side Handle(D), Side Grip, Depth Gauge, Grease Vessel (Tool does not come with bit.)

HR5202C 52mm - Adapted for SDS-MAX Shank Acc Pg. A065-079 **175** 

Rotary Hammer



High efficiency and unrivalled low level of vibration.

- 2 operation modes - hammering and hammering with rotation.
- Ergonomically designed handle with rubberized soft grip provides more control and comfort.
- Selectable two on/off switches on demolition mode.
- One-Touch Sliding Chuck enables easy bit change

Specifications:- 

Continuous rating input	1,510W
Capacity	Concrete (with T.C.T. bit) : 52mm (2") Concrete (with Core bit) : 160mm (6-5/16")
Impacts per minute (ipm)	1,100 - 2,250
No load speed (rpm)	150 - 310
Sound pressure level	99dB(A)
Sound power level	110dB(A)
Vibration level	Chiseling: 10.5m/s ² / Hammer drilling: 17m/s ²
Dimensions (L x W x H)	599x134x287mm (23-1/2"x5-1/4"x11-1/4")
Net weight	10.9kg (24.1lbs)
Power supply cord	5.0m (16.4ft)

Standard Equipment: Side handle (D), Side grip, Depth gauge, Grease vessel