

- CORDLESS
- FIXING / FASTENING
- DRILLING / IMPACT DRILLING
- CONCRETE DRILLING / DEMOLITION
- CUTTING [CONCRETE/ MASONRY/ METAL]
- MULTI TOOL
- GRINDING
- SANDING / POLISHING
- SAWING
- ROUTERING / PLANING
- CLEANING
- HEAT GUN / LASERS
- PNEUMATIC TOOLS
- GARDEN TOOLS
- GENERATORS

JS1602
1.6mm (16Ga)
Acc Pg. A086 459

Metal Shear

Slim motor housing and rear cover provides more control and better maneuverability.

- Conveniently located slide switch for one hand operation.

Specifications:-

Continuous rating Input	380W
Capacity	Steel up to 400 N/mm ² : 1.6mm
	Steel up to 600 N/mm ² : 1.2mm
	Steel up to 800 N/mm ² : 0.8mm
	Aluminum up to 200 N/mm ² : 2.5mm
Min. cutting radius	30mm (1-3/16")
Strokes per minute (spm)	4,000
Dimensions (L x W x H)	255x74x146mm (10"x2-15/16"x5-3/4")
Net weight	1.6kg (3.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Hex wrench

JS3201
3.2mm
Acc Pg. A086 303

Metal Shear

Robust design with elastomer coated handle provides easy operation

- Protector equipped under the body prevents from scratching by metal cutting piece, and enables smooth cutting.
- On-tool storage for Hex wrench

Specifications:- WITH MAKPAC

Continuous rating Input	710W
Capacity	Steel up to 400 N/mm ² : 3.2mm
	Steel up to 600 N/mm ² : 2.5mm
	Steel up to 800 N/mm ² : 1.5mm
	Aluminum up to 200 N/mm ² : 4.0mm
Min. cutting radius	50mm (2")
Strokes per minute (spm)	1,600
Dimensions (L x W x H)	213x90x239mm (8-3/8"x3-1/2"x9-3/8")
Net weight	3.4kg (7.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Shear blades set, Hex wrench, Thickness gauge

JN1601
1.6mm
Acc Pg. A086 411

Nibbler

Precise, burr-free curved and straight cuts from slim, yet powerful performer

- Cuts flat and corrugated sheet metal with the same die.
- Die rotates 360 degrees, large 1/4" stroke.
- Extremely light (weighs only 1.6kg).
- Built-in thickness gauge for convenience

Specifications:-

Continuous rating Input	550W
Capacity	Steel up to 400 N/mm ² : 1.6mm
	Steel up to 600 N/mm ² : 1.2mm
	Steel up to 800 N/mm ² : 0.8mm
	Aluminum up to 200 N/mm ² : 2.5mm
Min. cutting radius	Outside edge : 50mm (2")
	Inside edge : 45mm (1-3/4")
Strokes per min.	2,200
Overall length	261mm (10-1/4")
Net weight	1.6kg (3.6lbs)
Power supply cord	2.0m (6.6ft)

Standard Equipment: Hex Wrench, Wrench, Punch, Die

JN3201
3.2mm
Acc Pg. A086 303

Nibbler

Robust design with elastomer coated handle provides easy operation.

- Common blade with JN3200
- On-tool storage for Hex wrench

Specifications:- WITH MAKPAC

Continuous rating Input	710W
Capacity	Steel up to 400 N/mm ² : 3.2mm
	Steel up to 600 N/mm ² : 2.5mm
	Steel up to 800 N/mm ² : 1.0mm
	Aluminum up to 200 N/mm ² : 3.5mm
Min. cutting radius	Outside edge: 128mm (5-1/16")
	Inside edge: 120mm (4-3/4")
Strokes per minute (spm)	1,300
Dimensions (L x W x H)	225x90x254mm (8-7/8"x3-1/2"x10")
Net weight	3.4kg (7.4lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Punch Die, Wrench 50, Hex Wrench, Washer.