

6953 12.7mm (1/2")

Acc Pg. A032-036 **411**

Impact Wrench



Compact body (overall length: 233mm) with palm-fitting soft grip for superior handling.

- Removable belt clip can be attached on both sides of the tool.
- Externally accessible carbon brushes for easy maintenance.

Specifications:-



Continuous rating Input	280W
Capacity	Standard bolt: M10 - M16 (3/8" - 5/8") High tensile bolt: M8 - M12 (5/16" - 1/2") Square drive : 12.7mm (1/2")
Impacts per minute	0-3,000ipm
No load speed	0-3,000rpm
Max. fastening torque	150N.m (110ft.lbs)
Overall length	233mm (9-1/8")
Net weight	1.5kg (3.3lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Does not come with sockets.

TW0350 12.7mm (1/2")

Acc Pg. A032-036 **411**

Impact Wrench



Incredibly high torque of 350N.m (260ft.lbs).

- Rocker type switch for easy forward or reverse operation.
- Externally accessible carbon brushes for easy maintenance.

Specifications:-



Continuous rating Input	400W
Capacity	Standard bolt : M12 - M22 (1/2" - 7/8") High tensile bolt : M12 - M16 (1/2" - 5/8") Square drive : 12.7mm (1/2")
Impacts per minute	2,000
No load speed	2,000
Max. fastening torque	350N m (260ft.lbs)
Overall length	282mm (11-1/8")
Net weight	3.0kg (6.6lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Socket.

6906 19mm (3/4")

Acc Pg. A032-036 **100**

Impact Wrench



Powerful torque of 588N.m(441ft.lbs) for super-duty applications.

- Rocker type reversing switch for easy one handed forward or reverse operation.
- Slide handle adjusts 360degrees for operation convenience at any angle.
- Externally accessible carbon brushes for easy maintenance.

Specifications:-



Continuous rating Input	115V / 220V 850W 230-240V 620W
Capacity	Standard bolt: M16 - M22 (5/8" - 7/8") High tensile bolt: M16 - M20 (5/8" - 3/4") Square drive : 19mm (3/4")
Impacts per minute	1,600ipm
No load speed	1,700rpm
Max. fastening torque	588N.m (441ft.lbs)
Overall length	327mm (12-7/8")
Net weight	5.6kg (12.3lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Grip Assembly, Socket.

TW1000 25.4mm (1")

Acc Pg. A032-036 **153**

Impact Wrench



Robust high torque Impact Wrench for heavy-duty application.

- Incredibly high torque 1,000N.m
- Rocker switch provides easy reversing.
- Rubber bumper for tool body protection.
- Features hanging hook for comfortable operation.

Specifications:-



Continuous rating Input	1,200W
Capacity	Standard bolt: M24 - M30 (15/16" - 1-3/16") High tensile bolt: M22 - M24 (7/8" - 15/16") Square drive : 25.4mm (1")
No load speed	1,400rpm
Max. fastening torque	1,000N.m (738ft.lbs)
Overall length	382mm (15")
Net weight	8.6kg (19.9lbs)
Power supply cord	2.5m (8.2ft)

Standard Equipment: Socket 24-45, Grip

CORDLESS

FIXING / FASTENING

DRILLING / IMPACT DRILLING

CONCRETE DRILLING / DEMOLITION

CUTTING [CONCRETE/ MASONRY/ METAL]

MULTI TOOL

GRINDING

SANDING / POLISHING

SAWING

ROUTERING / PLANING

CLEANING

HEAT GUN / LASERS

PNEUMATIC TOOLS

GARDEN TOOLS

GENERATORS